


PRODUCTS CATALOGUE

"AT EASE IN YOUR CONSTRUCTION SITE"





Ritmo meets all your welding needs in your jobsite



The information and photos in this publication are not binding and RITMO S.P.A. is free to make any alterations without prior notice.



DVANTAGE RITMO



RITMO WORLDWIDE

Ritmo has professional distributors and resellers all over the world. Our staff is ready to assist you in English, Spanish, French, German, Arab, Italian, Russian and Portuguese.

TRAINING

From many years now, we have decided that the best way to grant a client/ distributor a perfect knowledge of our products Is to invest in custom training, in our own premises. These courses are aimed to teach how to operate the products in the best way, and how to supply the "first aid" when necessary.

PRESALES TECHNICAL ASSISTANCE

When a client or a potential client wants to buy us a product, it is our standard procedure to help find the best solution to its needs.

GLOBAL ADVICE

In such a technical field as ours, the customer requires the best assistance. Thanks to the experience developed along the years, and to the co-operation with several manufacturers, institutions, schools and training institutes, RITMO is able to give the most comprehensive advice to no matter which related issue. Our company is a long-time member of a UNIPLAST's (UNI-Italian National Plastics Standards Body) working group dedicated to the study and draw up of new standards within our field. The importance of this group is linked to the fact that the expansion of the plastic welding field ought to be followed by a crescent sensitivity for safety issues, so to have a sustainable and continuous growth. The working group prepares draws, hence present them to the UNI to be discussed and eventually transformed into new standards.

AFTER SALES TECHNICAL ASSISTANCE

Ritmo's Service Centre can solve all kind of technical issues, as well as overhaul our machines. Ritmo has other Service Centres abroad, linked to its official distributors.

STARTING AND TESTING

RITMO' technicians are prepared to make the starting and testing of workshop machines at the client' own premises, so that the fittings production can start almost immediately.





RED - RITMO EXTERNAL DEBEADER

External Debeader by RITMO S.p.A. covering a range from Ø 63 up to 1200 mm; 2" IPS ÷ 48" IPS

Designed to remove the external bead from a complete butt fusion welded joint.

The tool knocks onto the pipe bead, then alignment blocks slide against the pipe surface to guide it around the pipe. The blade cuts the under the bead and the handle helps pull the tool around the pipe, cutting the bead away. RED works on flat surfaces too and removes the bead from plastic sheets without the guides for pipes.

Available in three different sizes

- RED 63 125
- RED 90 400
- RED 400 1200





TECHNICAL FEATURES

Models	Working range
ivioueis	working range
RED 63 - 125	Ø 63 ÷ 125 mm; 2" IPS ÷ 4" IPS
RED 90 - 400	Ø 90 ÷ 400 mm; 3" IPS ÷ 14" DIPS
RED 400 - 1200	Ø 400 ÷ 1200 mm; 16" IPS ÷ 48" IPS
Material	HDPE - PP



BUTT FUSION MACHINES REFERENCE



		-0.00		C of		-			-			- 11				A				-		2502		Carrier P		0865762	10 mm / 11	B-199	
WORKING RANGE Ø mm	32	40	50	63	75	90	110	125	140	160	180	200	225	250	280	315	355	400	450	500	560	630	710	800	900	1000	1200	1400	160
GAMMA 160		40	50	63	75	90	110	125	140	160																			
DELTA 160 M	32	40	50	63	75	90	110	125	140	160																			
DELTA 200 M				63	75	90	110	125	140	160	180	200																	
BASIC 160		40	50	63	75	90	110	125	140	160																			
BASIC 200				63	75	90	110	125	140	160	180	200																	
BASIC 250					75	90	110	125	140	160	180	200	225	250															
BASIC 315						90	110	125	140	160	180	200	225	250	280	315													
BASIC 355								125	140	160	180	200	225	250	280	315	355												
COMPACT 355								125	140	160	180	200	225	250	280	315	355												
BASIC 160 EASY LIFE		40	50	63	75	90	110	125	140	160																			
BASIC 200 EASY LIFE				63	75	90	110	125	140	160	180	200																	
BASIC 250 EASY LIFE					75	90	110	125	140	160	180	200	225	250															
BASIC 315 EASY LIFE						90	110	125	140	160	180	200	225	250	280	315													
BASIC 355 EASY LIFE								125	140	160	180	200	225	250	280	315	355												
DELTA 500 EASY LIFE												200	225	250	280	315	355	400	450	500									
DELTA 630 EASY LIFE															280	315	355	400	450	500	560	630							
DELTA 500												200	225	250	280	315	355	400	450	500									
DELTA 630															280	315	355	400	450	500	560	630							
DELTA 800																				500	560	630	710	800					
DELTA 1000																						630	710	800	900	1000			
DELTA 1200																							710	800	900	1000	1200		
DELTA 1600 ECO / 1600 HDR																								800	900	1000	1200	1400	16
DELTA 250 TRAILER / MANUAL					75	90	110	125	140	160	180	200	225	250															
DELTA 355 TRAILER DELTA 355 ALL TERRAIN								125	140	160	180	200	225	250	280	315	355												
DELTA 500 TRAILER DELTA 500 ALL TERRAIN												200	225	250	280	315	355	400	450	500									
REMEDY 500 FA														250	280	315	355	400	450	500									
DELTA 630 TRAILER DELTA 630 ALL TERRAIN													225	250	280	315	355	400	450	500	560	630							
DELTA 1000 TRAILER																315	355	400	450	500	560	630	710	800	900	1000			
REMEDY 1000 EL																315	355	400	450	500	560	630	710	800	900	1000			
DELTA DRAGON 250 CNC					75	90	110	125	140	160	180	200	225	250															
DELTA DRAGON 315 CNC						90	110	125	140	160	180	200	225	250	280	315													
WORKING RANGE Ø mm	32	40	50	63	75	90	110	125	140	160	180	200	225	250	280	315	355	400	450	500	560	630	710	800	900	1000	1200	1400	16

WORKING RANGE Ø CTS	1"	11/4"	11/2"	2"																												_
WORKING RANGE Ø IPS					1"	11/4'	1½"	2"	3"	4"	5"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	42"	48"	52"	54"	63"
GAMMA 160					1"	11/4'	1½"	2"	3"	4"	5"																					
DELTA 160 M	1"	11/4"	11/2"	2"	1"	11/4'	1½"	2"	3"	4"	5"																					
DELTA 200 M								2"	3"	4"	5"	6"																		П		
BASIC 160 / BASIC 160 EASY LIFE					1"	11/4'	1½"	2"	3"	4"	5"																			П		
BASIC 200 / BASIC 200 EASY LIFE								2"	3"	4"	5"	6"																				
BASIC 250 / BASIC 250 EASY LIFE								2"	3"	4"	5"	6"	8"																			
BASIC 315 / BASIC 315 EASY LIFE									3"	4"	5"	6"	8"	10"																П		
BASIC 355 / BASIC 355 EASY LIFE										4"	5"	6"	8"	10"	12"	14"														П		
COMPACT 355										4"	5"	6"	8"	10"	12"	14"																
DELTA 500 / DELTA 500 EASY LIFE													8"	10"	12"	14"	16"	18"														
DELTA 630 / DELTA 630 EASY LIFE														10"	12"	14"	16"	18"	20"	22"	24"											
DELTA 800																			20"	22"	24"	26"	28"	30"								
DELTA 1000																					24"	26"	28"	30"	32"	34"	36"					
DELTA 48"																							28"	30"	32"	34"	36"	42"	48"			
DELTA 1600 ECO / DELTA 1600 HDR																									32"	34"	36"	42"	48"	52"	54"	63"
DELTA 250 TRAILER / MANUAL								2"	3"	4"	5"	6"	8"																			
DELTA 355 TRAILER DELTA 355 ALL TERRAIN										4"	5"	6"	8"	10"	12"	14"																
DELTA 500 TRAILER DELTA 500 ALL TERRAIN												6"	8"	10"	12"	14"	16"	18"	20"													
DELTA 630 TRAILER DELTA 630 ALL TERRAIN													8"	10"	12"	14"	16"	18"	20"	22"	24"											
DELTA 1000 TRAILER																14"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"					
REMEDY 1000 EL																14"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"					
WORKING RANGE Ø IPS					1"	11/4'	1½"	2"	3"	4"	5"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	42"	48"	52"	54"	63"

WORKING RANGE Ø DIPS	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	24"	30"	36"	42"	48"	54"	60"
GAMMA 160	3"	4"															
DELTA 160 M	3"	4"															
DELTA 200 M	3"	4"	6"														
BASIC 160 / BASIC 160 EASY LIFE	3"	4"															
BASIC 200 / BASIC 200 EASY LIFE	3"	4"	6"														
BASIC 250 / BASIC 250 EASY LIFE	3"	4"	6"	8"													
BASIC 315 / BASIC 315 EASY LIFE	3"	4"	6"	8"	10"												
BASIC 355 / BASIC 355 EASY LIFE		4"	6"	8"	10"	12"											
COMPACT 355		4"	6"	8"	10"	12"											
DELTA 500 / DELTA 500 EASY LIFE				8"	10"	12"	14"	16"	18"								
DELTA 630 / DELTA 630 EASY LIFE					10"	12"	14"	16"	18"	20"							
DELTA 800									18"	20"	24"						
DELTA 48"												30"	36"	42"			
DELTA 1600 ECO / DELTA 1600 HDR												30"	36"	42"	48"	54"	60"
DELTA 250 TRAILER / MANUAL	3"	4"	6"	8"													
DELTA 355 TRAILER DELTA 355 ALL TERRAIN		4"	6"	8"	10"	12"	14"										
DELTA 500 TRAILER DELTA 500 ALL TERRAIN			6"	8"	10"	12"	14"	16"	18"	20"							
DELTA 630 TRAILER DELTA 630 ALL TERRAIN				8"	10"	12"	14"	16"	18"	20"	24"						
DELTA 1000 TRAILER							14"	16"	18"	20"	24"	30"	36"				
REMEDY 1000 EL							14"	16"	18"	20"	24"	30"	36"				
WORKING RANGE Ø DIPS	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	24"	30"	36"	42"	48"	54"	60"





RITMO S.p.A. Via A. Volta, 35/37 - 35037 Bresseo di Teolo (PADOVA) ITALY

Ph. +39 049 9901888 Fax +39 049 9901993

> info@ritmo.it www.ritmo.it

